

# Crimp size hydraulic hose Olssons Compact+

ANV093

EN

<b>Working temperature, continuous</b>	-40 °C to +100 °C
<b>Working temperature max.</b>	125 °C
<b>Outer casing</b>	Smooth rubber casing
<b>Inner tube</b>	Oil resistant rubber
<b>Reinforcement</b>	Two braided steel inserts
<b>Oils</b>	Vegetable oils Synthetic oils Mineral oils
<b>Vacuum durability</b>	-0.95 bar (1/4", 3/8", 1/2") -0.80 bar (3/4", 1")
<b>Standards</b>	Exceeds EN857 2SC Exceeds ISO 11237-1 2SC



Size	Inner diameter (mm)	Outer diameter (mm)	Max. working pressure (bar)	Min. rupture pressure (bar)	Min. bending radius (mm)	Weight (g/m)
1/4"	6.4	13.1	450	1950	45	285
3/8"	9.5	17.1	385	1650	70	440
1/2"	12.7	20.3	345	1400	90	565
3/4"	19	27.7	280	1200	160	835
1"	25.4	35.6	200	900	210	1215

**Part number. 21203-xx**

**Punching in sleeve: 03400-xx**

Size	Ending	Crimp size
1/4"	04	18.2 mm
3/8"	06	20.6 mm
1/2"	08	23.5 mm
3/4"	12	31.1 mm
1"	16	39.4 mm

**Part number. 21204-xx**

Size	Ending	Crimp size	Punching in sleeve
1/4"	04	16.2 mm	001C-xx
1/2"	08	24,2 mm	03450-xx

**Part number. 21206-xx**

**Punching in sleeve: 03300-xx**

Size	Ending	Crimp size
1/4"	04	17,0 mm

The following crimp sizes apply when using Olssons i Ellös Compact+ together with our crimp sleeves:



Olssons i Ellös AB • Tel +46 304-751010  
Slätthultsvägen 12 • S-474 31 Ellös  
www.olssonparts.com • order@olssonparts.com

2023-11-08