

Crimp size hydraulic hose SEL Powerstream 4 SH

22191-12, 22191-16, 22191-20 & 22191-24

ANV117

EN

Working temperature, continuous	-40 °C to +100 °C
Outer casing	Wound rubber casing
Inner tube	Oil resistant rubber
Reinforcement	Four spiral wound steel inserts
Oils	Vegetable oils Glycol based oils Mineral oils
Standards	DIN 20023 PART 2 TYPE 4SH EN856 4 SH TS 10548 / EN 856 4 SH ISO 1307



Size	Inner diameter (mm)	Outer diameter (mm)	Max. working pressure (bar)	Min. rupture pressure (bar)	Min. bending radius (mm)	Weight (g/m)
3/4"	19	32	420	1680	280	1500
1"	25.4	38.4	380	1520	340	2065
1 1/4"	31.8	45.2	350	1400	460	2425
1 1/2"	38.1	53	290	1160	560	3235

The following crimp size applies when using SEL Powerstream 4 SH together with nipples and crimp sleeves in the Spiralfit series.

Part number. 22191-xx

Punching in sleeve: 05400-xx

Size	Ending	Crimp size
3/4"	12	36.7 mm
1"	16	44.5 mm
1 1/4"	20	52.0 mm
1 1/2"	24	59.7 mm